

Tylö steam generators

Steam generators Tylö VA

A powerful, fully automatic steam generator with a large water tank, making it ideal for public facilities. Requires connection to electricity and water supplies. Convertible 1-phase/3-phase. IP rating: IP 45. Add your choice of control panel.

Steam 6 VA

(Art. no. 6620 2020)
6 kW output. Size 570 x 485 x 224 mm.

Steam 9VA-K

(Art. no. 6620 3021)
9 kW output. Size 570 x 485 x 224 mm.

Steam 12 VA

(Art. no. 6620 4020)
12 kW output. Size 570 x 485 x 224 mm.

Steam 18 VA

(Art. no. 6620 5020) 18 kW output. Size 615 x 485 x 445 mm.

Steam 24 VA

(Art. no. 6620 6020)
24 kW output. Size 615 x 485 x 445 mm.

Tylö Steam VB

A compact steam generator with the same high quality materials, functions and features as the VA models, but with a smaller water tank to ensure rapid heating-up times in small and medium-sized private steam rooms. IP rating: IP 23. Add your choice of control panel.



www.tylo.com/steamgenerators

Control panels



CC 10

Electronic control panel for SE 6 and SE 8 heaters. Designed for wall-mounted installation outside the sauna. Max. 3-10 hours running time. 0-10 hour preset. Including external temperature sensor. (See installation instructions for location.) Size: 100 x 150 mm, depth 30 mm. IP 24.

(Art. no. 7121 3000) Surface mounting
(Art. no. 7101 3040) Recessed mounting



CC 50

(Art. no. 7121 4005)
Display for time and temperature, switch for lighting, and security code function. Programmable for 1, 3, 12 and 24 hours or continuous operation. 0-10 hour preset. Size: 130 x 190 mm, depth 27 mm. IP 24.

h1

(Art. 7200 1000)

Electronic control panel, equipped with touch-control that not only displays the temperature and running time, but can also be programmed to start up to 24 hours in advance and run for between 0 and 23 hours. The control panel allows you to regulate lighting in the sauna, set the maximum temperature, switch between Fahrenheit and Celsius, use a 12-hour or 24-hour format, set different languages, and more advanced settings and test options.

Tylö h1 control panel can replace Tylö's CC10 and CC50 models. Size: 140 x 80 mm, depth 19 mm. Use with our RB relay box when installing our SDK/SD sauna heater.



CC 300

(Art. no. 7111 5150)

CC300 can be set to run between 1 and 24 hours and has a display that indicates temperature, remaining operating time, day and time. In addition, the CC 300 comes with a switch for lighting, Swedish/English instructions, memory features, security code and energy-saving, stand-by function. CC300 has an integral weekly timer for optional automatic on/off operation and stand-by mode at preselected times on the days of your choice. The control panel can also be controlled from external units. Size: 130 x 190 mm, depth 27 mm. IP 24.



External switch

(Art. no. 9090 8040)

On/off switch to control the sauna from locations other than where the CC control panel is installed.



Decorative frame

(Art. no. 9000 1050) Matt brushed
(Art. no. 9000 1051) Gloss brushed
(Art. no. 9000 1052) High-gloss



www.tylo.com/controlpanels